

EUROLINE

mark II



New DESIGN, same proven Quality

A unique low profile front face and a more shallow body offers more interior space conventional designs without compromising security.

-3 sizes to choose from

Body and Door

The body and door are constructed with Megasafe's high-security composite matrix material forming a barrier able to resist attacks by various mechanical and electro-mechanical tools available today.

-Body barrier thickness: 2" (50mm)

-Door barrier thickness: 1.57" (40mm)

Features:

Manganese anti-drill hard steel plates protect the locks and vital areas

A smooth operating gear driven mechanism extends chrome plated bolts 1.2" (30mm) into individual bolt chambers.

An adjustable shelf standard on all 3 models allow vertical adjustment by every 2" (50mm)

Hinges are manufactured of a solid steel block and allow opening the door to 180°

2 holes for anchoring on bottom of the safe for securely bolting down the safe to the floor

Lock options:

The euroline safes are fitted with 2 independent high-security locks:

a user friendly electronic lock and a double bitted mechanical key lock together offer a superior level of security

Electronic lock features:

1 Manager Code

1 User Code

Time Delay function up to 99min can be optionally set which enable a delayed opening of the safe lock and door if needed

Wrong try penalty delay resists possible code guessing

Fire Resistant:

The safe's composite construction offers fire protection of 1 hr

High-Security Residential / Small Business Safe



mark II

the perfect Security Solution for your home or business
.....with style



Dimensions & Weights:

MODEL	INSIDE DIMENSIONS			OUTSIDE DIMENSIONS			APPROX. WEIGHT
	H	W	D*	H	W	D*	
MK 1216 Size 40	12.0" (300mm)	16.0" (400mm)	11.0" (280mm)	16.0" (400mm)	19.7" (500mm)	17.0" (440mm)	297 lbs (135 kg)
MK 2116 Size 65	21.0" (550mm)	16.0" (400mm)	11.0" (280mm)	25.6" (650mm)	19.7" (500mm)	17.0" (440mm)	420 lbs (190 kg)
MK 2620 Size 75	25.6" (650mm)	19.7" (500mm)	13.4" (340mm)	29.5" (750mm)	23.6" (600mm)	19.7" (500mm)	564 lbs (256 kg)

*Add 2" (50mm) to outside depth for handle and locks



9V Battery Drawer is located conveniently in the inner top side of the safe's door. The lock notifies you when the battery is weak with 6 continuous beeps just after entering your code. As a safety, the lock can always be alternatively powered up from the front face of the lock so you never have to worry about being locked out do to a low battery.

Authorized Dealer:



In effort to continuously innovate and develop high-security products, the manufacturer reserves the right to incorporate any improvements and alter any specifications without prior notice.